

**F**  
**Fissacavi**  
 Cable clamps  
**Serre cables**  
 Befestigungskabeln

**G**  
**Morsettiere a faston**  
 Tab terminal blocks  
**Borniers à faston**  
 Klemmkasten mit faston

**F1**


PA 107-277-277C-277S



S (mm<sup>2</sup>) 3x0.75÷3x1.5/5x1  
 work.temperature (°C) -5÷125

**G1**

PA 32-262



S (mm<sup>2</sup>) 2.5  
 V (Volts) 450  
 I (A) 24 (15A tab-to-tab)  
 work.temperature (°C) -5÷85

**F2**


PA 206



S (mm<sup>2</sup>) 3 x 0.75÷3 x 4.0  
 work.temperature (°C) -5÷125

**G2**

PA 80-81-262



S (mm<sup>2</sup>) 2.5  
 V (Volts) 450  
 I (A) 24  
 work.temperature (°C) -5÷110

**F3**

PA 238-268



S (mm<sup>2</sup>) 3x0.75÷3x4/5x6  
 work.temperature (°C) -5÷125/150

**G3**

PA 300-300/4-300/6



S (mm<sup>2</sup>) 1.5  
 V (Volts) 250  
 I (A) 17.5  
 work.temperature (°C) -5÷125

**F4**

FX 5773

**NEW**



S (mm<sup>2</sup>) 1.0  
 V (Volts) 250  
 I (A) 13.5  
 work.temperature (°C) -10÷125

**G4**

PA 21-108



S (mm<sup>2</sup>) 2.5  
 V (Volts) 450  
 I (A) 15  
 work.temperature (°C) -5÷125

**ABCDEFGG**

**famiglie di prodotto** / product families /  
**famille de produit** / Produkt Familien

**S (mm<sup>2</sup>)**

**sezione cavo** / wire size  
**section du cable** / Kabelschnitt

**V (Volts)**

**tensione nominale** / rated voltage /  
**tension nominal** / Nennspannung

**I (A)**

**corrente nominale** / rated current /  
**max. courant** / max. Strom

Ratings according to IEC standards

COMERCIAL  
**tecas**